

## CURRENT SENSING SELECTION GUIDE

Construction Type	Series	Case Size (In.)	Power	Resistance	TCR	Tolerance
2-Terminal	MPA	1206, 2512	1W~3W	0.5mΩ~56mΩ	±50ppm/°C~ ±150ppm/°C	±0.50%~±1.00%
	MPC	0201~1206	1/4W~1W	1mΩ~50mΩ	±50ppm/°C~ ±200ppm/°C	±0.50%~±1.00%
	WEL Short Side	0603~4527	1/2W~4W	1mΩ~700mΩ	±50ppm/°C, ±100ppm/°C	±0.50%~±1.00%
	WEL Short Side Auto	0603~2512	1/2W~2W	3mΩ~570mΩ	±50ppm/°C, ±100ppm/°C	±0.5.%~±1.00%
	WEL Long Side	0508~2043	1W~5W	1mΩ~100mΩ	±50ppm/°C~ ±150ppm/°C	±0.50%~±3.00%
	WEL Long Side Auto	0508~0830	1W~3W	1mΩ~100mΩ	±50ppm/°C, ±100ppm/°C	±0.50%~±1.00%

Note: This is a product overview, not exact electrical specification. Please refer to product datasheet or contact TFT for the most up-to-date specifications.

## CURRENT SENSING SELECTION GUIDE

Construction Type	Series	Case Size (In.)	Power	Resistance	TCR	Tolerance
2-Terminal	WKL	0603~4527, 0508~2043	1/2W~5W	1mΩ~700mΩ	±50ppm/°C, ±100ppm/°C	±0.50%~±1.00%
	WLM	0805~4527	1/2W~5W	0.25mΩ~500mΩ	±50ppm/°C~ ±100ppm/°C	±0.50%~±5.00%
4-Terminal	CPC	0306	1/3W	1mΩ~50mΩ	±50ppm/°C~ ±150ppm/°C	±1.00%
	WRL	1206, 2512	1/3W~1W	0.5mΩ, 1mΩ~100mΩ	±30ppm/°C~ ±100ppm/°C	±0.30%~±1.00%
	CPA	0612	1W	0.5m~25mΩ	±50ppm/°C~ ±200ppm/°C	±0.50%~±1.00%
	FCP	0306~0612	1/2W~1W	0.5mΩ~5mΩ	±75ppm/°C~ ±100ppm/°C	±0.50%~±1.00%

Note: This is a product overview, not exact electrical specification. Please refer to product datasheet or contact TFT for the most up-to-date specifications.